For Residential and Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

Series 911 Combination Fill Valve and Backflow Preventer

Size: 1/2" (15mm)

Series 911 combination fill valve and backflow preventer consists of a Model 9D backflow preventer and Model 1156F feed water pressure regulator in one pre-assembled unit. This valve is designed for use on boiler feed lines to provide make-up water to the boiler and prevent backflow when supply pressure fails below system pressure.

Features

- Pre-assembled for ease of installation
- Easy service accessibility
- High capacity fill valve for quick system filling and purging

Options

- -"" union NPT x NPT connections
- -S union solder x NPT connections
- -QC Union Quick-Connect x NPT connection
- B- all bronze body construction union NPT x NPT connections
- w/press**** Press inlet x x press outlet (non union)

Viega ProPress[®] connections are optional factory installed fittings on each end of the approved/certified assembly.

Specifications

A combination fill valve and backflow preventer shall be installed on the boiler feed line to provide make-up water to the boiler. The valve shall contain a Watts Regulator Model 9D backflow preventer and Model 1156 feed water pressure regulator. The combination fill valve and backflow preventer shall be a Watts Series 911.



911



The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



Pressure – Temperature

Maximum Temperature: 212°F (100°C) Maximum Working Pressure: 100psi (6.9 bars) Adjustment Range: 10-25psi (68.7 – 172.4 kPa) set at 15psi (103.4 kPa)

Dimensions – Weights



MODEL	SIZE	(DN)	DIMENSIONS				WEIGHT	
			A		В			
	in.	тт	in.	тт	in.	тт	lbs.	kgs.
911	1/2	15	8 ¹ / ₂	216	5¼	133	4.2	1.9
911S	1/2	15	8 ¹ /2	216	5¼	133	4.2	1.9
911-QC	1/2	15	8 ³ ⁄4	222	5¼	133	4.2	1.9
B911	1/2	15	8 ¹ /2	216	5¼	133	4.2	1.9
B911S	1/2	15	8 ¹ / ₂	216	5¼	133	4.2	1.9
B911-QC	1/2	15	8 ³ ⁄4	222	5¼	133	4.2	1.9

Consult factory for dimensions with press fittings.

