

Model: AE4430Z-AA1A
Product Description

Type:	Reciprocating Compressors
Application:	HBP/CBP - High/Commercial Back Pressure
ProductDescription:	R-404A/R-407A/R-448A/R-449A/R-452A
Voltage/Frequency:	115V ~ 60Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE (R-407A)	115V ~ 60HZ	3236	816	948	411	7.87	1.98	2.31	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-449A)	115V ~ 60HZ	3128	789	917	409	7.64	1.93	2.24	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-448A)	115V ~ 60HZ	3128	789	917	409	7.64	1.93	2.24	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-452A)	115V ~ 60HZ	3261	822	956	427	7.64	1.93	2.24	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-404A)	115V ~ 60HZ	3450	869	1011	446	7.74	1.95	2.27	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	10
Weight Unit of Measure:	KG
Displacement (cc):	5.16
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	284.9

Electrical

Voltage Range (50 Hz):	
Voltage Range (60 Hz):	103-127
Locked Rotor Amps (LRA):	32
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	5.1
Max. Continuous Current (MCC in Amps):	7.96
Motor Resistance (Ohm) - Main:	1.65
Motor Resistance (Ohm) - Start:	3.44
MotorType:	CSIR

Overload Type:
Relay Type:

Agency Approval

CE Listed, cURus Recognized