

Model: AE2410A-AA1A

Product Description

Type:	Reciprocating Compressors
Application:	LBP - Low Back Pressure
Refrigerant:	R-12
Voltage/Frequency:	115V ~ 60Hz
Version:	N/A



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE (R-12)	115V ~ 60HZ	1098	277	322	273	4.03	1.01	1.18	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)
ASHRAE (R-12)	115V ~ 60HZ	1098	277	322	273	4.03	1.01	1.18	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

General

Evaporating Temp. Range:	-40°C to -10°C (-40°F to 14°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	10
Weight Unit of Measure:	KG
Displacement (cc):	9.39
Oil Type:	Synthetic Alkylate
Viscosity (cSt):	32
Oil Charge (cc):	380

Electrical

Voltage Range (50 Hz):	
Voltage Range (60 Hz):	103-127
Locked Rotor Amps (LRA):	28.5
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	3.11
Max. Continuous Current (MCC in Amps):	5.45
Motor Resistance (Ohm) - Main:	2.32
Motor Resistance (Ohm) - Start:	4.55
Motor Type:	CSIR
Overload Type:	
Relay Type:	

Agency Approval

CE Listed, cURus Recognized